



Defining and Managing KPIs for Logistics Optimization: A Critical Analysis of Container Utilization Rate, Cost per Unit Transported, and GHG Emissions

Defining and Managing KPIs for Logistics Optimization: A Critical Analysis of Container Utilization Rate, Cost per Transported Unit, and GHG Emissions

Author: Ivan de Matos

Graduated in Logistics from the Leonardo Da Vinci University Center

Postgraduate in Human Resources Management, from the Leonardo da Vinci University Center

Summary

This article discusses the design and governance of **key performance indicators (KPIs)** in intermodal logistics operations, focusing on three key metrics: **container utilization rate, cost per unit transported, and greenhouse gas (GHG) emissions**. We propose a framework that integrates **rigorous operational definition, data standardization, collection methods**, and **managerial use** anchored in **trade-offs** between efficiency, resilience, and sustainability. We articulate literature from **operations management, transportation economics, and carbon accounting** to show how seemingly technical choices—such as **denominators, measurement windows, cargo mix**, and **emissions scopes**—alter the **performance narrative** and **capital allocation** (CHRISTOPHER, 2016; CHOPRA; MEINDL, 2016; UNCTAD, 2020; WORLD BANK, 2020; GHG PROTOCOL, 2011; SMART FREIGHT CENTRE, 2019).

Keywords: logistics; KPIs; container; logistics costs; emissions; GHG.

Abstract

This paper examines the design and governance of **key performance indicators (KPIs)** in intermodal logistics, focusing on three backbone metrics: **container utilization rate, cost per transported unit, and greenhouse gas (GHG) emissions**. We propose a framework that integrates **rigorous operational definitions, data standardization, measurement methods**, and **managerial use** anchored in the **trade-offs** among efficiency, resilience, and sustainability. Drawing on **operations management, transport economics, and carbon accounting**, we show how seemingly technical **choices—denominators, measurement windows, job mix**, and **emissions scopes**—reshape the **performance narrative** and **capital allocation** (CHRISTOPHER, 2016; CHOPRA; MEINDL, 2016; UNCTAD, 2020; WORLD BANK, 2020; GHG PROTOCOL, 2011; SMART FREIGHT CENTRE, 2019).

Keywords: logistics; KPIs; container; logistics costs; emissions; GHG.

1. Fundamentals and scope of logistics KPIs: design principles, standardization and decision-making use

The discussion on logistics KPIs needs to begin with a **principle of utility**: an indicator is only good if it **guides decisions**—capacity allocation, investment prioritization, contract design—and **reduces ambiguity** in coordination between links.

This requires three layers: **a clear operational definition** (what is measured, where, and when), **a measurement method** (sources, formulas, windows, missing data handling), and **usage governance** (thresholds, responsible parties, rights of action). Without this three-pronged approach, metrics become "decorative panels" that multiply noise rather than generate action (CHRISTOPHER, 2016; ISO 22301, 2019). In intermodal chains, the risk of **semantic confusion** is high: "utilization," "unit cost," and "emissions" can mean different things at ports, railways, highways, and operators, leading to **spurious comparisons** without a common dictionary (WORLD E

The second principle is **measurement properties**. Indicators must be **reliable** (same method yields same results), **valid** (they measure what they intend to measure), **sensitive** to relevant operational changes, and **robust** to short-term noise. In logistics, **temporal granularity** and **segmentation by service** (route, cargo type, equipment, customer) are crucial to avoid **the law of averages**: an improvement in one service can be masked by a degradation in another, generating erroneous conclusions overall (CHOPRA; MEINDL, 2016). Therefore, it is recommended to publish KPIs by **window/service** and only then compose volume-weighted **indices**.

The third premise relates KPIs to **trade-offs**. **Container utilization rates** tend to improve with **consolidation** and **the addition of stops**, but this can **worsen lead times** and **variance**, increasing **inventories** and **capital costs**; **cost per unit transported** decreases with **economies of scale**, but can **weaken resilience** by concentrating gateways and lengthening routes; **GHG emissions** decrease due to **modal shift** and **increased load factor**, but may **conflict** with service windows or **limit optionality** (SMART FREIGHT CENTRE, 2019; UNCTAD, 2020). The dashboard design should make these conflicts **explicit**, with **hierarchical goals** (minimum service, resilience, efficiency, sustainability), avoiding **local optimizations** that destroy global value.

The fourth point is **standardization**. GHG emissions, for example, must follow standards such as **the GHG Protocol – Scope 3 (Category 4/9)** and **EN 16258** for transportation, with consistent **emission factors** by fuel and mode; **the use of containers** requires conventions on **payload** (weight vs. cubic capacity), **exclusions** (empty reefer *pre-trip*), and **backhaul treatment**; **the cost per unit** must specify whether it is **pure freight** or **cost-to-serve** (including handling, demurrage/detention, storage, and working capital) (GHG PROTOCOL, 2011; EN 16258, 2012; CHOPRA; MEINDL, 2016). Without this basis, **internal and external** comparisons lose their meaning.

The fifth element is **data quality and lineage**. Logistics KPIs arise from **TOS/PCS**. (ports), **WMS/TMS**(storage/transportation), **telemetry** (AIS, ELDs), **billing** and



energy/fuel systems. To be auditable, there must be a **reconciliation trail** and **versioning**: how were **TEUs, tons, kilometers, fuel**, and **costs** obtained, aggregated, and cleaned? This due diligence reduces **contractual disputes** (indexing to reliability, *gain-sharing*) and prevents **greenwashing** in emissions (IAPH, 2020; WORLD BANK, 2020). Whenever possible, **APIs** and **data dictionaries** should be part of the contract.

The sixth aspect is **scope of control**. A useful KPI distinguishes **what to control** from what to simply **monitor**. **Container utilization** can be partially controlled by consolidation, **match-back**, and **triangulation policies**; **cost per unit** by **modal mix, contracts, and route redesign**; **emissions** by **fuel, load factor, speed, and modal shift**.

KPIs outside the manager's scope become **sources of frustration**; therefore, the dashboard must display **associated levers** and **thresholds** that trigger **action rights** (CHRISTOPHER, 2016; SIMCHI-LEVI; KAMINSKY; SIMCHI-LEVI, 2008).

The seventh principle deals with **decision-making rhythm**. KPIs with **high volatility** require **moving windows** and **smoothed signals** (e.g., weighted averages), while capital decisions require **stable series**; **issuances** can be closed **monthly** and audited **annually**; **utilization** and **unit cost** require **weekly/daily cadence** to allow for quick course corrections (SMART FREIGHT CENTRE, 2019; ISO 22301, 2019). The **lag time** between measurement and action is itself a maturity KPI.

Finally, the eighth foundation is **organizational alignment**. KPIs should be incorporated into **S&OP/S&OE** and the **budget cycle**, with **targets and bonuses** linked to **OTIF, cost-to-serve, load factor**, and **carbon intensity**. **Training, tabletop exercises**, and **After Action Reviews** transform indicators into **learning** and **continuous improvement**, consolidating a **resilient operational framework** in which **data** drives **decisions** and **decisions** produce **auditable results** (SHEFFI, 2015; ISO 22301, 2019).

2. Container Utilization Rate: Definition, Measurement, Biases, and Decisions

Container utilization rates measure how much of a container's **useful capacity** (weight or volume) is actually occupied by paying cargo. In simple terms, **utilization (weight)** can be defined as *cargo weight / (maximum container payload)* and **utilization (volume)** as *cargo volume / (cubic capacity)*; on mixed routes, **conversion factors (stowage factors)** are used to reconcile **weight vs. cubic capacity** (NOTTEBOOM; RODRIGUE, 2021). At the fleet level, weighted average utilization can be reported by **TEU-km** or by **trip**, distinguishing between **headhaul** and **backhaul** to avoid **an averaging effect** that masks structural imbalances (UNCTAD, 2020). When publishing the metric, it is critical to clarify **the basis**.

(weight/volume) and **what exclusions** were applied.

The first challenge is **data quality**. In many environments, **net weight** and **cubic capacity** are not standardized across systems; **EDI** and **shipping documents** arrive with **gaps**; **mixed loads** require **estimates**. It is recommended to create **layers of data collection**: *level 1* per **manifest/data lake** (estimation), *level 2* per **WMS/TMS** (operational capture), and *level 3* per

Physical audit/sampling on critical routes. **Imputation and outlier rules** should be published to ensure **consistency** and **comparability** (WORLD BANK, 2020; IAPH, 2020). Without this, the use becomes an **opinionated number**.

The second point is the **appropriate denominator**. For **dry 40'**, **payload** is a typical limiting factor; for **bulky products** (tissue, light e-commerce), **cubic capacity** dominates; in **reefer**, part of the capacity is "lost" to equipment and **segregation**; for **dangerous goods**, **compatibility** reduces occupancy. Therefore, comparing **utilization** across **product classes** without **standardization** creates **unfairness** and **perverse incentives** (CHOPRA; MEINDL, 2016). A best practice is to measure **utilization adjusted** for the SKU's **physical limit** (weight or volume) and publish **benchmarks by family**.

The third aspect is **operational biases**. The pursuit of **maximum utilization** encourages **waiting to consolidate**, increasing **lead time** and **variance**; during peak periods, late consolidation **worsens OTIF** and **triggers demurrage/detention**. On the other hand, **denser** containers can increase **damage** and **safety risks**, with **hidden costs**. The optimal decision balances **marginal utilization** with **time and risk costs**, often via **response curves** estimated in **digital twins** of the corridor (SIMCHI-LEVI; KAMINSKY; SIMCHI-LEVI, 2008; CHRISTOPHER, 2016). Therefore, the KPI must be accompanied by **service limits** and **exception rules**.

The fourth theme is **structural underutilization** due to **geographic imbalance**. In flows with **strong headhaul and weak backhaul**, **average utilization** falls even with **operational excellence**; part of the solution lies in **triangulation**, **match-back**, and **interorganizational container pools** to reduce **empty repositioning** and increase **effective utilization** (UNCTAD, 2020; DREWRY, 2021). Here, the KPI should be read alongside **equipment availability indices** and **repositioning rates**, otherwise **the operator may be blamed** for **market structure**.

The fifth point is **integration with sustainability**. **Greater utilization** reduces **emissions per ton-km** by **diluting** fuel consumption per unit, but it can **increase absolute emissions** if **consolidation** requires **longer routes** or **waiting times**; in addition, **modal shift**

To reduce carbon, it can temporarily **reduce utilization**. Therefore, it is recommended to publish **carbon intensity (gCO₂e/t-km)** in parallel with utilization and **to explicitly state route/modal offsets** (SMART FREIGHT CENTRE, 2019; IMO, 2020). The correct narrative avoids **efficiency greenwashing**.

The sixth element is **contracts and incentives**. **SLAs** that **reward only utilization** can **penalize service** and **resilience**; **gain-sharing** mechanisms aligned with **cost-to-serve** and **emissions balance objectives**. In **port congestion**, **conditional demurrage/detention** policies can **unlock boxes** and allow for **higher utilization**.

without punishing the customer for **systemic causes** (WORLD BANK, 2020; IAPH, 2020). The KPI should inform **contractual reviews** and **exception policies**.

The seventh theme is **cadence and visualization**. **Usage by window** (hour/day) in **heatmaps** by **service and gateway** helps **identify patterns** and **match-back opportunities**; **dashboards**

with **dispersion** (not just average) reveal **volatility** and **special causes**. On critical routes, **thresholds** activate **playbooks**: below X% for Y days, **trigger alternative consolidation**; above Z%, **review damage risks** and **stowage policy** (CHRISTOPHER, 2016; WORLD BANK, 2020).

Finally, the eighth aspect is **learning**. **After-Action Reviews** during **seasonal peaks** and **disruption events** should update **consolidation rules**, **exception policies**, and **contracts**. External (sectoral reports) and **internal** (between corridors) **benchmarking** avoids **local myopia**. When well governed, the **utilization rate** ceases to be vanity and becomes **an integrated lever** of **cost-to-serve**, **OTIF** and **carbon intensity**, with defined **responsibilities and rights of action** (UNCTAD, 2020; NOTTEBOOM; RODRIGUE, 2021; SMART FREIGHT CENTRE, 2019).

3. Cost per unit transported: operational definition, *cost-to-serve* and management decisions

The **cost per unit transported** metric seems trivial at first glance—dividing logistics expenses by a volume denominator—but its **decisive power** depends on the **operational definition** and **scope of costs** adopted. In intermodal chains, there are four dominant denominators: **(i)** cost per **TEU-km** or **ton-km**, suitable for modal benchmarking; **(ii)** cost per **order**, useful for fragmented B2B portfolios; **(iii)** cost per **SKU or product family**, which internalizes differences in density and *time value*; **(iv)** cost per service **window** (route/service/gateway), which explains trade-offs between reliability and expense (CHOPRA; MEINDL, 2016; WORLD BANK, 2020). In any case, it is essential to state whether the indicator covers **pure freight** or **cost-to-serve (including terminal handling, drayage/chassis, warehousing, demurrage/detention, insurance, working capital, and contingency shipments)**, since strategic decisions—such as **multi-gateway, off-dock**, or **capacity options**—move items outside of freight but within the **cost-to-serve** (UNCTAD, 2020; SHEFFI, 2015).

Calculating **the numerator** requires reconciling **fixed and variable costs** and, ideally, employing an **activity-based costing system**. In networks with a high service *mix*, **ABC/TDABC** distributes *overheads* (planning, scheduling, customs control, control towers, PCS) by **cost drivers** linked to actual resource use (trips, *stops*, *touches*, crane time, *truck turntime*), mitigating average distortions (CHOPRA; MEINDL, 2016; KAPLAN; ANDERSON, 2007). The quality of the apportionment determines the usefulness of the KPI: if *overheads* peak and **congestion costs** (detention, *premium surcharges*) remain “outside” the numerator, the indicator **underestimates** the advantage of solutions that reduce variance — for example, **extended windows** and **dry ports** (WORLD BANK, 2020; IAPH, 2020).

On the denominator side, the choice between **TEU-km** and **ton-km** alters comparisons between **light-volume** products (light e-commerce, *tissue*) and **heavy-compact** products (metals, chemicals). Best practices combine **two views**: cost per **ton-km** to reflect physical-energetic effort, and cost per **order/SKU** to capture **operational complexity** (touch points,

documentation, inspections) not explained by mass (CHRISTOPHER, 2016; OECD/ITF, 2016). In **refrigerated container services**, including **energy/plug-in** and “unsaleable” capacity losses (equipment, segregations) avoids *bias* against *reefers* when compared to *dry* (UNCTAD, 2020).

Freight and energy volatility recommends incorporating **bands** or **indexes** into the KPI. In fluctuating BAF/GRI and correlated **diesel/bunker** environments, the cost per unit should present **scenarios** (base, high, low) or **sensitivity curves** by mode, showing **indifference points** between **all-water** and **land-bridge**, or between **road** and **intermodal/rail** (EIA, 2021; UNCTAD, 2020). By connecting the KPI to **signal posts** (decrease in *schedule reliability*, docking queues, rail *slot*), S&OE gains **triggers to migrate the modal mix** before the *spike* destroys margins (SEA-INTELLIGENCE, 2021; SIMCHI-LEVI; KAMINSKY; SIMCHI-LEVI, 2008).

The KPI's connection to **reliability** and **time** is structural. **Minutes** on the dock and **hours** in the yard/gate become **margin points** when translated into **safety stocks, contingency shipments**, and **lost sales**, reinforcing the need for **integrated dashboards** that display **cost per unit along with TTR/TTS, OTIF** and **demurrage/detention (SHEFFI, 2015; PONOMAROV; HOLCOMB, 2009)**. Without this integration, **average cost** improvements can hide **a worsening in variance** that **increases** the total **cost of serving** — a typical *mean trap* in networks with bottlenecks (WORLD BANK, 2020; NOTTEBOOM; RODRIGUE, 2021).

In **contracts and incentives**, index part of the **freight** or **handling** to **service indicators** (e.g., *on-time, truck turn time, dwell*) aligns the KPI with the goal of **reducing TTR** and **backlog compression**. **Gain-sharing**, which shares **avoided losses** (detention drop, premium freight, air shipments) encourages operators to **open windows, activate off-dock**, and **divert** flow when thresholds are crossed, even if this **momentarily raises** the unit cost “on the spreadsheet” (IAPH, 2020; WORLD BANK, 2020). The focus shifts from **cost per TEU** to **cost-to-serve and preserved margin**, language that convinces finance (CHRISTOPHER, 2016).

Heterogeneity by **SKU/customer** requires a **differentiated service policy**. **Time-sensitive** products accept **higher unit costs** in exchange for **lead time** and **low variance**; *commodities* accept **longer inventory/route**. **ABC curves for value and criticality**, coupled with **window/service**, avoid “shelf optimums” that reduce a KPI but **increase lost sales** or **emissions** (SMART FREIGHT CENTRE, 2019; CHOPRA; MEINDL, 2016). The dashboard should allow **simulating combos: multi-gateway + off-dock + capacity option** versus “stock only”, comparing **cost per unit** and **TTR**.

Finally, **data quality and auditing** support credibility. Integrate **TOS/PCS, WMS/TMS, billing**, and **energy/fuel** via **APIs** and **metric dictionaries**. published reduces disputes and **greenwashing costs**; *After Action Reviews* and **reconciliations** periodic adjustments adjust imputation rules (outliers, voids, *backhauls*) and ensure **intertemporal comparability** (IAPH, 2020; OECD/ITF, 2016). In summary, the KPI “cost

per unit” only provides good guidance when it is **explainable, comparable, decision-sensitive**, and **coupled** resilience and **sustainability**.

4. GHG emissions: scopes, calculation methods and management use in the decision portfolio

Measuring **GHG emissions** in logistics requires **recognized standards** and transparent methodological **deliberations**. The **GHG Protocol** consolidates the distinction between **Scope 1** (owned fuels), **Scope 2** (purchased electricity), and **Scope 3**—especially **Categories 4 (upstream transportation)** and **9 (downstream transportation)**—, while **EN 16258** and the **GLEC Framework** offer specific guidelines for **freight transportation** and **fuel life cycle** (GHG PROTOCOL, 2011; EN 16258, 2012; SMART FREIGHT CENTRE, 2019). For operational decisions, the baseline indicator is **carbon intensity (gCO₂e/ton-km or TEU-km)**, which can be enriched by **WTT/TTW (well-to-tank / tank-to-wheel)**, **NO_x/SO_x**, and, in air, **radiative forcing** adjustments when politically required (SMART FREIGHT CENTRE, 2019; IMO, 2020). Declaring **inventory boundaries, emission factors**, and **data quality** (tiering) avoids incomparable numbers.

Data quality can follow a tiered ladder: **Tier 1 (standard factors)** by mode and fuel; **Tier 2 (operational data)** such as actual diesel, bunker, and yard/reefer electricity consumption; **Tier 3 (telemetric measurements)** by trip/service (speed, *idling, cold ironing*), with *matching* to **ETA/ETD** and **yard tasks** (SMART FREIGHT CENTRE, 2019; IAPH, 2020). The higher the **tier**, the greater the **predictive capacity** to analyze **trade-offs of load factor, speed** (slow steaming), **route**, and **modal shift**. The annual audit should clarify **errors and uncertainties** and **recalculate series** when factors are updated, ensuring **comparability** (GHG PROTOCOL, 2011).

The relationship between **container utilization** and **emissions** is **non-linear**. Increasing **load factor** reduces intensity (gCO₂e/ton-km), but can **increase absolute emissions** if it involves **waiting** to consolidate, **longer routes**, or **re-handling** at *hubs* (NOTTEBOOM; RODRIGUE, 2021; UNCTAD, 2020). Therefore, it is recommended to report **intensity along with absolute emissions** and **service indicators** (OTIF, TTR), making **trade-offs explicit**. On *reefers*, **set-point** and **plug-in** (shore power) **decisions** change the hourly emissions profile; in yards, **electrification** and **selective automation** shift **Scope 1 to Scope 2** emissions, requiring attention to **grid factors** (WORLD BANK, 2020; IMO, 2020).

Modal **shift** is the classic decarbonization lever, but its **net value** depends on **time** and **capacity**. Migrating **from road to rail/intermodal** reduces **intensity** per ton-km; however, if **slots are scarce** or **transfers** multiply *touches* and *dwells*, **TLC** and **TTR** can **worsen**, producing **contingency** (air) expeditions that cancel out gains (OECD/ITF, 2016; CHOPRA; MEINDL, 2016). Operational scenarios need to **co-simulate** emissions, cost and service level, using **digital twins** that include **energy, efficiency factor load and reliability** to prescribe **efficient portfolios** (IVANOV; DOLGUI, 2020; SHEFFI, 2015).

In the ocean, IMO 2020 has already reduced SO_x, and pre-2021 discussions on CII/EEXI point to **efficiency per ton-mile; slow steaming** reduces emissions per voyage but **increases inventory in transit** and may **require additional ships** to maintain frequency, with **ambiguous effects** on total emissions (IMO, 2020; UNCTAD, 2020). In **ports, shore power** and **yard electrification** shift the marginal emissions curve, conditioned by the **local electricity matrix; PCS** that expose **queue/anchorage** and coordinate **windows** reduce maritime-land **idling**, delivering carbon and service **co-benefits** (IAPH, 2020; WORLD BANK, 2020).

WTT+TTW accounting avoids bias in comparisons between **diesel, LNG and electricity**. Fuels with **low TTW emissions** can have **high WTT**; electrification shifts emissions to **Scope 2** and depends on **grid intensity**; **LNG** reduces **NO_x/SO_x** and **CO₂ TTW** but may have significant **methane leakage upstream** (SMART FREIGHT CENTRE, 2019). For decision-making purposes, publishing **WTT and TTW intensity** by mode and **uncertainty margins** protects the KPI from **overly optimistic** interpretations and aligns the portfolio with **realistic targets**.

In **contracts and incentives, carbon indexes** can integrate **SLAs** and **gain-sharing**: discounts or bonuses tied to **gCO₂e/ton-km reductions** maintained without **worsening OTIF/TTR**; “**green**” **capacity options** (slots on services/railways with higher intensity), exercisable when **emissions** or **energy** bands require climate resilience (IAPH, 2020; CHRIS-TOPHER, 2016). **Extended windows, off-dock**, and **multi-gateway** are also **climate instruments** when they reduce **idling** and **rehandling**, even if they slightly increase unit cost—hence the importance of integrated **cost-to-serve + carbon + service panels** (WORLD BANK, 2020; OECD/ITF, 2016).

Governance and transparency prevent *greenwashing*. Publishing **methodologies, factors, tiers**, and **uncertainty limits**; aligning with the **GHG Protocol/EN 16258/GLEC**; submitting **samples** to **independent verification**; and incorporating **emissions** into **S&OP/S&OE** with **triggers** (e.g., migrating X% to rail when **diesel bandwidth** and **network factor** become the **dominant option**) transform the KPI into **an executive lever** (GHG PROTOCOL, 2011; SMART FREIGHT CENTRE, 2019). Post-peak **AARs** and **quarterly reviews** keep the system **adaptive**, updating **portfolios** as technology, energy, and regulations evolve.

Finally, the **emissions KPI** needs to **align** with **utilization** and **cost per unit** within **efficient boundaries**. In many networks, the **combination of "adequate utilization (without waiting too long)" + smart scheduling + off-dock to reduce dwell + calibrated modal mix"** dominates single-cause solutions, reducing **gCO₂e/ton-km, TTR**, and **TLC** simultaneously (SHEFFI, 2015; IVANOV; DOLGUI, 2020; WORLD BANK, 2020). The result is a **portfolio of KPIs** that not only measures, but **guides** choices with **responsibilities, thresholds, and rights of action** defined.

5. Integration of the three KPIs in S&OP/S&OE, control towers and contracts: from metrics to the right of action

The integration between **container utilization rate, cost per transported unit** and **GHG emissions** begins with a **governance design** that links metrics to **decision-making rituals** (S&OP/S&OE), **pre-authorized rights of action** and **numerical thresholds** that

trigger operational *playbooks*. In **S&OP**, the three KPIs serve as **simultaneous constraints and targets**: minimum service levels (OTIF), **cost-to-serve ceilings**, target **utilization** ranges by product family, and **carbon budgets** by corridor; in **S&OE**, these targets become **triggers** with deadlines and responsible parties, reducing **decision-making latency** in the event of shocks (ISO 22301, 2019; CHRISTOPHER, 2016). This architecture only works if there is a common **metric dictionary** and auditable **data lineage**, avoiding "two truths" in the same room (WORLD BANK, 2020; IAPH, 2020).

In the **S&OP** cycle, it is recommended to treat KPIs in **two layers: base planning** (demand, capacity, modal/gateway redesign) and **scenario planning** with **freight/energy** and **reliability** bands that show utilization \times **TTR \times gCO₂e/ton-km** *trade-offs* before approving the portfolio and budget. The committee should receive **efficient frontiers** produced by digital twins: for each mix of **bridge inventory, multi-gateway, off-dock, and capacity options**, display the **TLC** and the **area of the expected resilience triangle**, with **Operational VaR** ranges under freight tails and delays (SHEFFI, 2015; PONOMAROV; HOLCOMB, 2009; CHOPRA; MEINDL, 2016). Thus, the discussion migrates from "averages" to **protected downside**.

In **S&OE**, the key word is **rhythm**. Daily/weekly **dashboards** in the control tower should show **utilization by window/service, cost per unit** (base and *cost-to-serve* with detention/storage/capital), and **carbon intensity**, always **alongside flow KRIs** (schedule reliability, queue/anchorage, *truck turn time, rail slot*), so that deviations are visible **before** they become losses (SEA-INTELLIGENCE, 2021; IAPH, 2020). Clear **triggers**—e.g., *Utilization (adjusted) < X% for Y days + dwell > Z h*—trigger **alternative consolidation, extended windows, off-dock activation**, or **gateway diversion**, with *owners* defined (ISO 22301, 2019; WORLD BANK, 2020).

Inter-organizational control towers are the **engine** of this integration: they consolidate **AIS/TOS/PCS/WMS/TMS/energy**, apply **imputation methods** and reconciliation routines (TOS \rightarrow PCS \rightarrow billing) and publish **versions** of the series with **latency SLA** and **audit logs**. At this layer, **APIs** and **standards** (EDIFACT/X12/REST) ensure comparability and enable **contractual indexing** to reliable data (OECD/ITF, 2016; IAPH, 2020). Without this infrastructure, **KPIs become opinions**, and **SLAs** degenerate into version disputes—a scenario familiar during congestion peaks (WORLD BANK, 2020).

In **contracts**, KPIs should be **instruments**, not *decorations*. **Contingency SLAs** can index part of the price to **reliability and fluidity** (OTIF, *truck turn time, dwell*), establish **conditional exemptions** from **demurrage/detention** when the root cause is systemic, and link **bonuses/penalties** to the **reduction of gCO₂e/ton-km** without sacrificing service (IAPH, 2020; WORLD BANK, 2020). **Capacity options** and **deviation clauses** should have **objective triggers** (**decrease** in *schedule reliability, queues, fuel bands*) defined from the dashboards, so that **costly actions** are only taken when **the preserved margin** exceeds the premium (SIMCHI-LEVI; KAMINSKY; SIMCHI-LEVI, 2008; CHRISTOPHER, 2016).

Shop floor incentives must avoid **perversities**. Exclusively rewarding **utilization** can lead to **delays** and **breakdowns**; rewarding only **unit cost** can

dehydrate resilience and worsen **OTIF**; subsidizing **emissions** alone can **force modal shifts** without capacity. The solution is a **weighted basket**: utilization targets **adjusted** by the SKU limit, **cost-to-serve** per window, and **carbon intensity** with **service limits** and **exception bands** (SMART FREIGHT CENTRE, 2019; CHOPRA; MEINDL, 2016). In peak environments, **prioritizing by time value** legitimizes decisions that **sacrifice utilization** to **save revenue**.

Operational **digital twins** connect planning and execution: receive **signals** (reliability, queues, energy) and test **playbooks** to see **how much** each action reduces **TTR** and **TLC** and **how** it affects **utilization** and **gCO₂e/ton-km**. This *testing technology* avoids "spreadsheet optimums" and anchors **CAPEX/OPEX requests** on **response curves** (IVANOV; DOLGUI, 2020; NOTTEBOOM; RODRIGUE, 2021). By bringing the " *what-if*" into routine, the company transforms **KPIs** into **operational policy**, not *scorecards*.

Selective transparency with the ecosystem closes the loop: publishing **methodologies, data tiers**, and **uncertainties**; adhering to the **GHG Protocol/EN 16258/GLEC**; sharing **performance dashboards** with partners and, where appropriate, authorities; and submitting **samples** for **independent verification** strengthens legitimacy and **reduces litigation** (GHG PROTOCOL, 2011; SMART FREIGHT CENTRE, 2019; IAPH, 2020). The result is an **Operational Resilience Regime** in which **KPIs ÿ triggers ÿ actions ÿ auditable metrics** (ISO 22301, 2019; SHEFFI, 2015).

Finally, the **cadence** needs to be explicit: **weekly** reviews for *tactical* (S&OE), **monthly** for *tactical-strategic* (S&OP), and **quarterly** for **portfolio and contracts**; post-peak **AARs** update **thresholds** and **exception rules**; **training** maintains proficiency in reading dashboards and operating *playbooks*. Without **cadence and training**, even the best KPIs **don't translate into behavior** (SHEFFI, 2015; ISO 22301, 2019).

6. Resilience metrics (TTR/TTS, OTIF, VaR) as a governance "envelope" for cost, utilization, and carbon

We call the **resilience envelope** the set of **operational limits** defined by **TTR/TTS** (time to degrade/recover), **OTIF** (delivered service level), and **Operational VaR/Expected Shortfall** (tail loss). **Cost per unit, utilization**, and **gCO₂e/ton-km** must optimize **within** this envelope—never at the expense —, under penalty of ephemeral gains of **increasing variance** and **destroying margin** in shocks (SHEFFI, 2015; PONOMAROV; HOLCOMB, 2009; CHOPRA; MEINDL, 2016). The envelope makes **explicit** that efficiency and sustainability **are constraints**, not mere aspirations.

TTR /TTS should be measured by **node** and by **corridor**, with sufficient granularity to capture **backlogs** and **reinforcement loops**. In ports and intermodal, **berthing time, quay productivity, yard occupancy, truck turn time, and rail slots** are **predictors** of TTR; the control tower needs to **simulate** how **extended windows, off-dock**, and **diversions** move the network back to the subcritical regime (WORLD BANK, 2020; SEA-

INTELLIGENCE, 2021). Setting **TTR targets** per scenario creates a “suffering ceiling” that cannot be breached by decisions that only **lower the TEU**.

OTIF is the **customer's compass** and should be **co-monitored** with **utilization**: consolidating to increase load factor without degrading **OTIF is optimal** ; consolidating **with** window degradation and **demurrage/detention is a false gain**. In **imbalanced** and **peak** environments , **prioritization by time value** and **exception policies** (by critical SKU) preserve **revenue**.

better than blind utilization targets (CHRISTOPHER, 2016; NOTTEBOOM; RODRIGUE, 2021). **Dashboards should** show OTIF **dispersion** , not just averages, to expose margin-consuming **tails** .

Operational **VaR/Expected Shortfall** translates **service** and **cost** into financial terms: what is the worst plausible **loss** (extra cost, *lost sales*, *freight premium*) at 95%/99%? In portfolios with capacity and **multi-gateway options** , VaR **falls** even if the **average cost** rises slightly—a rational tradeoff in **time-sensitive** sectors (SIMCHI-LEVI; KAMINSKY; SIMCHI-LEVI, 2008; SHEFFI, 2015). Incorporating VaR into the envelope prevents **static optimizations** from passing the committee without proving **tail protection**.

KRIs form the **anticipatory** edge of the envelope. Persistent drops in **schedule reliability**, bunker /diesel *spikes* , out-of-band **queuing/anchoring** , **truck turntime explosions** , and limiting **rail slot utilization** are **precursory signals** that require **automatic action**.

according to *the playbook* (IAPH, 2020; SEA-INTELLIGENCE, 2021; EIA, 2021). Defining **numerical thresholds**, **sources** , and **those responsible** prevents the envelope from being **rhetorical** and ensures **reaction time** before **backlogs** grow **superlinearly**.

The envelope also organizes **efficient frontiers** between **utilization × TTR × carbon**.

Graphs displaying **gCO₂e/ton-km** vs. **TTR** under **cost-to-serve** bands reveal **dominant combinations** —e.g., **adequate utilization + smart scheduling + off-dock** —that reduce **carbon** and **time** at a slight incremental cost; single-cause solutions, such as **slow steaming** without recalibrating **inventories** and **frequency**, can **violate** TTR/OTIF and **widen** the resilience triangle (SMART FREIGHT CENTRE, 2019; OECD/ITF, 2016; IMO, 2020).

The envelope, therefore, is a **portfolio tool**, not just an audit tool.

In the **executive report**, the envelope becomes **the master chart**: boardroom **dashboards** show **OTIF**, **TTR/TTS**, **VaR**, **cost-to-serve**, **utilization** , and **carbon intensity** , along with **methodologies** and **uncertainties**; **public targets** and **barometers** (IAPH/World Bank) provide **legitimacy** and external **benchmarking** (WORLD BANK, 2020; IAPH, 2020; ISO 22301, 2019). In this language, **CAPEX/OPEX** requests become a matter of **avoided losses** and **TTR reductions**, not aesthetic *slides* .

Finally, the envelope is **alive**. Quarterly **AARs** recalibrate **thresholds**, update **emission factors** and **imputation rules** (tiers, WTT/TTW), and revise utilization **denominators** .

by changing the *mix* and incorporating **new evidence** (e.g., *driver shortages*, climate seasonality). **Training** and **simulations** maintain proficiency; **independent audits**

preserve credibility (GHG PROTOCOL, 2011; SMART FREIGHT CENTRE, 2019; ISO

22301, 2019). In short, the envelope makes **efficiency, service, and sustainability** permanent **co-pilots** of decisions — not occasional passengers.

7. *Benchmarking* and *gain-sharing* between links: designing incentives without perversities

The starting point for serious *benchmarking* of **container utilization, cost per unit, and emissions** is **methodological standardization**: the same metric dictionary, the same time windows, the same segmentation by **service/route/gateway** and **product family**, with clarity regarding **denominators** (ton-km, TEU-km, order, SKU) and scopes (**pure freight** vs. **cost-to-serve; WTT/TTW** in carbon). Without this, cross-comparisons generate **illusions of efficiency** and **contractual injustices**, especially when there are **structural headhaul/backhaul** imbalances that depress average utilization and distort carbon intensities (CHOPRA; MEINDL, 2016; SMART FREIGHT CENTRE, 2019; UNCTAD, 2020). A robust practice is to publish tiered *benchmarks* : by window/service (base), by corridor (aggregate), and a **corporate index** weighted by time/revenue value.

The second foundation is **data quality and lineage**. *Benchmarks* should indicate data **tiers** (average factors, operational consumption, telemetry), **sources** (TOS/PCS, WMS/TMS, billing, energy), **imputation rules** , and **independent auditing** by sampling, preventing supposed "improvements" from being the result of **accounting changes** rather than actual productivity (IAPH, 2020; WORLD BANK, 2020; GHG PROTOCOL, 2011). The absence of a reconciliation trail—for example, between published **dwel** and billed **detention** —turns *benchmarking* into a version dispute and neutralizes *gain-sharing* (OECD/ITF, 2016).

The third pillar is **mix adjustment**. The comparison of cost/ton-km and gCO₂e/ton-km needs to **be disaggregated** by **density, reefer vs. dry, hazardousness** , and **criticality** (time value), otherwise operations that serve inherently more expensive SKUs or those with a lower load factor will be penalized. The solution is to use **adjusted indices** (e.g., *utilization adjusted to the limit*, cost-to-serve by **window/service** , and **carbon intensity** with WTT/TTW) and publish, alongside the indices, **mix compositions** for contextual reading (CHRISTOPHER, 2016; SMART FREIGHT CENTRE, 2019; UNCTAD, 2020). This adjustment reduces **perverse incentives** to "avoid" difficult cargo.

In the *gain-sharing* design , the rule must share **avoided losses** measured in **currency**: drop in **demurrage/detention**, premium freight , **contingency** shipments and **TTR** converted into saved working **capital** , in addition to the **reduction in gCO₂e/ton-km** weighted by the carbon shadow price, when applicable. The reference is a frozen **baseline** (window/service) and a **counterfactual** generated by a **digital twin** or adjusted historical series, with *washout* of exogenous effects (fuel, tariffs) to avoid compensating for "tailwind." (SHEFFI, 2015; IVANOV; DOLGUI, 2020; WORLD BANK, 2020). The earnings *pool* finances **extended windows, off-dock** , and **extra trains**, creating a **virtuous cycle**.

To **avoid perversities**, *gain-sharing* cannot **benefit utilization or unit cost in isolation** . One - dimensional targets create **delays** in consolidation (worsening OTIF/TTR), **risk of breakdowns** , and **hidden carbon** due to *idling*; carbon-only targets can **force modal shifts**.

without capacity, increasing costs and degrading service. The antidote is a **weighted basket: adjusted utilization + cost-to-serve + gCO₂e/ton-km within a resilience envelope (TTR/TTS, OTIF, VaR)** that acts as a **hard constraint** (CHOPRA; MEINDL, 2016; SMART FREIGHT CENTRE, 2019; SHEFFI, 2015). This way, one does not buy "cheap" efficiency that blows the tail of risk.

Another consideration is **timing**. Earnings should be calculated using **seasonally adjusted rolling windows** and explicitly addressed **peaks**, so that operators **invest** when it matters most (harvests, *peak season*). **Seasonal clauses** that increase the gain *-sharing split* at peak times align incentives with the **marginal elasticity** of measures such as **windows** and **additional trains** (SEA-INTELLIGENCE, 2021; WORLD BANK, 2020). Without this *timing*, gains appear **outside** from the window of pain and the ecosystem regresses to improvisation.

Independent verification is part of the contract: sampling of **dwell, turn time, utilization, fuel**, and **emissions** by a neutral third party, with **ACIs** and **reprocessing rules** when data gaps exceed tolerances. In carbon, it's worth using **GLEC tiers** and recalculating retrospectively when **factors** change, preserving **intertemporal comparability**. (SMART FREIGHT CENTER, 2019; GHG PROTOCOL, 2011). At cost, **ABC/TDABC** audited ensures that *overheads* and **congestion costs** do not "disappear" (KAPLAN; ANDERSON, 2007; WORLD BANK, 2020).

There are also **regulatory and competitive constraints**. In markets with **alliances** and **vertical integration**, *gain-sharing* and **container pools** must comply with **antitrust** and **non-discrimination**, with **neutral access** and **minimal data transparency**; otherwise, the remedy becomes a barrier to entry (OECD/ITF, 2016; HARALAMBIDES, 2019). The solution is to standardize **APIs**, publish **methodologies** and **aggregate targets**, and maintain **multi-stakeholder committees** for technical arbitration, reducing asymmetry and opportunism (IAPH, 2020).

Finally, *benchmarking* and *gain-sharing* only create value when **they feed back into S&OP/S&OE** and **budgets**. Quarterly targets for **TTR reduction and cost-to-serve reduction** and **carbon intensity** should **release funding** from a **resilience fund** for **off-dock, windows, selective automation**, and **capacity options**, with phase **gates** tied to proven **avoided loss** (SHEFFI, 2015; ISO 22301, 2019). It is in this chain—measuring, comparing, distributing gains, and reinvesting—that the KPI dashboard ceases to be **decorative** and becomes a **driver of governance**.

8. Implementation Roadmap : Goals, Cadence, and Independent Verification

The *roadmap* begins with a **materiality assessment**: mapping **critical corridors, A/B SKUs by time value, likely bottlenecks** (port, *drayage*, rail, compliance), **energy profile**, and **data maturity by tier**. The result is a **map of risks and levers**.

that links each KPI to **KRIs** (reliability, queue/docking, *turn time*, slots) and available **action rights** — for example, "*Adjusted utilization < X% + dwell > Y* h ÿ **activate off-dock/windows**; *LPG < Z% for 3 weeks* ÿ **exercise capacity/deviation option**" (SEA-

INTELLIGENCE, 2021; ISO 22301, 2019; WORLD BANK, 2020). This **control panel** defines where to start.

Phase 1 (0–90 days): Build the **minimum viable dashboard** and **metric dictionary**. Integrate **TOS/PCS, WMS/TMS, billing**, and **energy/fuel** via **APIs**, publish **formulas** (utilization, cost-to-serve, gCO₂e/ton-km) and data **lineages**, and establish **latency SLA** and **imputation rules**. In parallel, run a **pilot** in a **corridor/window** with a **digital twin** to calibrate **response curves** (utilization × TTR × carbon) to **extended windows, off-dock, multi-gateway**, and **options**, creating **efficient frontiers** for S&OP (IVANOV; DOLGUI, 2020; CHOPRA; MEINDL, 2016).

Phase 2 (90–180 days): Institutionalize the **interorganizational control tower**, with **S&OE rituals** (daily briefings, weekly *war rooms*), **pre-authorized triggers**, and **playbooks** actionable. **Contracts** adopt a new logic: **contingency SLAs, reliability indexing, conditional demurrage/detention exemptions, capacity options with objective thresholds** anchored in the dashboard's KPIs/KRIs (IAPH, 2020; WORLD BANK, 2020; SIMCHI-LEVI; KAMINSKY; SIMCHI-LEVI, 2008). This phase reduces **decision-making latency** and gives metrics **teeth**.

Phase 3 (6–12 months): Scale **structural buffers** and **technical standardization**. Implement **dry ports/off-dock, chassis cohorts, seasonal rail contracts**, and **packaging/labeling/EDI-API standards** for **plug-and-play substitutability** between gateways, reducing **requalification time** and **diversion costs** (OECD/ITF, 2016; CHRISTOPHER, 2016). In this phase, formalize **gain-sharing** with **baseline** and **independent verification**, enabling self-financed **resilience funds** for **avoided losses** (SHEFFI, 2015).

Phase 4 (12–24 months): Prioritize **modular capacity** and **selective automation** where the twin shows **high marginal gain** in **TTR** per unit of capital: **phased berths, partial yard automation, additional STS, scalable rail corridors, shore power/yard electrification** with attention to **WTT/TTW** (WORLD BANK, 2020; IMO, 2020). Structure **availability payments** tied to **SLAs** and **TTR/OTIF** targets and **gCO₂e/ton-km**, reducing demand risk and accelerating *payback* (SHEFFI, 2015).

The *roadmap* requires explicit **goals and cadence**. **Weekly** for *tactical* (utilization/cost/OTIF KPIs and flow KRIs), **monthly** for S&OP (efficient frontiers and *mix*) modal/gateway) and **quarterly** for **portfolio** and **contracts**, with post-peak AARs to review **thresholds** and **exception rules** (ISO 22301, 2019; CHRISTOPHER, 2016). Public metrics (turnaround, *dwell*, reliability) and sector **barometers** increase **legitimacy** and **execution discipline** (IAPH, 2020; WORLD BANK, 2020).

Independent verification provides credibility and prevents cost and carbon *greenwashing*. For emissions, apply **GLEC/EN 16258/GHG Protocol** with **clear tiers, uncertainty bands**, and **recalculation** when factors change; for costs, audit **ABC/TDABC** and reconciliations with **detention/storage**; for utilization, audit **weights/cubes** by sampling and **match-back rules** (SMART FREIGHT CENTRE, 2019; GHG PROTOCOL, 2011; KAPLAN;

ANDERSON, 2007). The audit must be **operationally friendly**: focus on **risk-based sampling** and **API-first**.

Human capital is a prerequisite for success. Training teams in **dashboard reading, digital twin operations, options contracts**, and **trigger-based S&OP/S&OE**; establishing **internal certifications**; and running monthly table **simulations** consolidates **repeatable capabilities**.

(CHRISTOPHER, 2016; SHEFFI, 2015). **Bonuses** linked to **reduced TTR, cost-to-serve** and **carbon intensity** align behavior with strategy, avoiding **local optimizations** that erode service.

Finally, the *roadmap* requires a **financing framework** that translates KPIs into **bankable assets**. **Resilience funds** capture *gain-sharing* and finance **off-dock, windows**, and **selective automation**; **parametric insurance** and **capacity options** with **verifiable triggers** (LPG, queues, *dwell*) protect against **downside**; **modular capex** with **availability payments** enables larger projects (SHEFFI, 2015; SEA-INTELLIGENCE, 2021). This chain of events converts **measurement** into **action**, **action** into **results**, and **results** into **scale**.

— essence of **KPI governance** that optimizes **cost, service and carbon** simultaneously.

Conclusion

The analysis developed throughout this article argues that **logistics KPIs only create value when they cease to be "numbers on a dashboard" and become decision-making mechanisms with attached rights of action**. This requires **unambiguous operational definitions, standardized measurement methods**, and **governance** that links metrics to **S&OP/S&OE rituals, playbooks**, and contracts. By treating **container utilization rate, cost per unit transported**, and **GHG emissions** as a **tripod** —efficiency, cost-to-serve, and sustainability—we avoid local optimizations that erode service and margins in times of stress, anchoring choices in the **resilience envelope** (TTR/TTS, OTIF, and VaR) as **hard constraints** (CHRISTOPHER, 2016; CHOPRA; MEINDL, 2016; SHEFFI, 2015).

In the first axis, we show that **container utilization** is a **conditional metric**: it improves with consolidation, *match-back*, and triangulation, but can **degrade OTIF** and **increase risk** when it leads to excessive waiting and densification. A correct interpretation requires distinguishing **physical constraints** (weight vs. cubic capacity), **headhaul/backhaul, and product classes**.

(dry, reefer, hazardous materials), in addition to publishing **utilization adjusted** to the limit and **dispersion** by service window. In markets with **structural imbalance** and port bottlenecks, **interorganizational container pools** and **conditional demurrage/detention policies** are levers to increase effective use without punishing the wrong link (UNCTAD, 2020; NOTTEBOOM; RODRIGUE, 2021; WORLD BANK, 2020).

On the second axis, **cost per unit transported** only provides good guidance when migrating from **pure freight** to **cost-to-serve**, incorporating **terminal handling, drayage/chassis, warehousing, demurrage/detention, contingency shipments**, and **working capital**. The adoption of **ABC/TDABC** reduces apportionment biases and highlights the cost of variance (delays, queues, rolling), allowing for the comparison of **structural buffers** (multi-gateway, *off-dock*) and **contractual options**.

avoided loss and **reduced TTR**. Without this perspective, decisions that reduce the cost of TEU “on the spreadsheet” **increase** the total cost when measuring what really matters to the business (KAPLAN; ANDERSON, 2007; SHEFFI, 2015; IAPH, 2020).

In the third axis, **GHG emissions** need to move beyond *greenwashing* and into **auditable accounting: the GHG Protocol (Scope 3, Cat. 4/9), EN 16258** , and the **GLEC Framework** ensure **clear boundaries**, data **tiers** (averaging factors ÷ actual consumption ÷ telemetry), and the **WTT/TTW distinction**. **Carbon intensity (gCO₂e/ton-km)** should be reported **alongside** absolute emissions, **utilization** , and **service level**, as **apparent gains** in intensity can hide **waiting and re-handling** that increase total emissions. Decisions such as **slow steaming, modal shift** , and **yard/shore power electrification** need to be evaluated **across the portfolio**, with effects on **TTR, OTIF** , and **TLC** (GHG PROTOCOL, 2011; EN 16258, 2012; SMART FREIGHT CENTRE, 2019; IMO, 2020).

A central finding is that **data and standards** are the invisible infrastructure of this agenda. **Port Community Systems (PCS), Digital Single Windows** , and **APIs** between **TOS/WMS/TMS/energy** They reduce **information asymmetry**, cut **latency** , and allow **contracts to be indexed** to reliable metrics. **Data dictionaries, lineage/auditing** , and **regular publication** of **turnaround, dwell, and reliability data** create legitimacy and **reduce litigation**, especially when **contingency SLAs** and **conditional demurrage/detention exemptions** come into play (IAPH, 2020; WORLD BANK, 2020; OECD/ITF, 2016; ISO 22301, 2019).

We also argue that **interorganizational control towers** and **digital twins** are the link between **metrics** and **action**. By coupling **DES/SD/ABM** with **freight/energy bands** and **precursor signals** (schedule *reliability* decline , bunker/diesel *spikes* , queuing/docking), companies can **test playbooks** before activating them, estimating **response curves**: how much **extended windows, off-dock** , and **multi-gateway diversions** reduce **TTR** and **TLC**, and how they affect **utilization** and **gCO₂e/ton-km**. This operational realism avoids “spreadsheet optimums” and anchors **CAPEX/OPEX** requests in **avoided losses** (IVANOV; DOLGUI, 2020; SEA-INTELLIGENCE, 2021; EIA, 2021).

Literature and practice converge on **mitigation portfolios** that combine **physical buffers** (bridge stocks for *time-sensitive* SKUs), **structural buffers** (multi-gateway, *off-dock*, seasonal rail contracts), and real **options** (capacity reservations, *box pools*) with **objective triggers**. **Efficient frontiers** show that, in many corridors, the *combo* “**adequate utilization (no waiting), smart scheduling and off-dock**” dominates monocausal solutions, reducing **carbon** and **TTR** with a slight incremental cost per unit — **a rational exchange** when measured by **VaR/Expected Shortfall** of service (SHEFFI, 2015; NOTTEBOOM; PALLIS, 2020; CHOPRA; MEINDL, 2016).

At the **contractual level**, **gain-sharing** should distribute **avoided losses** (reduction in detention, premium freight and contingency shipments; reduction in TTR and gCO₂e/ton-km) over a **baseline** auditable, with **washout** of exogenous effects. **One-dimensional targets** (only utilization, only cost, only carbon) generate **perversities**; the correct design uses a **weighted basket within the resilience envelope** and observes **antitrust/non-discrimination** in

data pools and exchanges (IAPH, 2020; OECD/ITF, 2016; HARALAMBIDES, 2019; DREWRY, 2021).

We also proposed a four-phase **roadmap** : (i) minimum viable panel and metric dictionary; (ii) institutionalization of the tower with **pre-authorized triggers** and **contingency/option SLAs**; (iii) scaling of **structural buffers** and **technical standardization** for *plug-and-play* replacement ; (iv) investments in **modular capacity and selective automation**.
financed by **availability payments**. **Continuous training, AARs** , and **independent verification** preserve credibility and keep the organization in a **resilient operating regime** (ISO 22301, 2019; CHRISTOPHER, 2016; SHEFFI, 2015).

From a financial-executive perspective , the shift in perspective is unequivocal: **from average cost per TEU to margin preservation, loss avoidance** , and **tail protection**. **Operational VaR** makes **physical inventory, structural buffers** , and **options** comparable , while **carbon budgets** and **TTR/OTIF targets** function as **constraints**. This translation creates a **common language** between operations and the board and accelerates evidence-based approvals (PONOMAROV; HOLCOMB, 2009; SEA-INTELLIGENCE, 2021; WORLD BANK, 2020).

In short, **defining and managing KPIs** for **utilization, cost, and carbon** is **governance engineering**: standardizing, measuring, auditing, **connecting to action rights** , and **reinvesting earnings**. When **data** becomes infrastructure and **contracts** become **execution engines**, supply chains evolve from a reactive logic to a **predictable and adaptive regime**, in which **efficiency, resilience and sustainability** cease to compete with each other and begin to **co-optimize** economic and operational results, even under **geopolitical and tariff volatility** (CHRISTOPHER, 2016; NOTTEBOOM; RODRIGUE, 2021; SMART FREIGHT CENTRE, 2019).

References (up to 2021)

CHOPRA, S.; MEINDL, P. *Supply Chain Management: Strategy, Planning, and Operation*. 6. ed. Boston: Pearson, 2016.

CHRISTOPHER, M. *Logistics & Supply Chain Management*. 5. ed. Harlow: Pearson, 2016.

CLARKSONS RESEARCH. *Container Intelligence Quarterly*. London: Clarksons Research, 2021.

DREWRY. *Container Forecaster*. London: Drewry Maritime Research, 2021.

EIA – US ENERGY INFORMATION ADMINISTRATION. *Short-Term Energy Outlook*. Washington, DC: EIA, 2021.

EN 16258. *Methodology for Calculation and Declaration of Energy Consumption and GHG Emissions of Transport Services (freight and passengers)*. Brussels: CEN, 2012.



GHG PROTOCOL. *Corporate Value Chain (Scope 3) Accounting and Reporting Standard*. Washington, DC: WRI/WBCSD, 2011.

HARALAMBIDES, HE Gigantism in container shipping, ports and global logistics: a time-lapse into the future. *Maritime Economics & Logistics*, vol. 21, p. 1–60, 2019.

IAPH – INTERNATIONAL ASSOCIATION OF PORTS AND HARBORS. *COVID-19 Port Economic Impact Barometer*. Antwerp: IAPH, 2020.

IMO – INTERNATIONAL MARITIME ORGANIZATION. *IMO 2020 Sulfur Cap: Guidance and Impacts*. London: IMO, 2020.

ISO. *ISO 22301:2019 — Security and Resilience — Business Continuity Management Systems — Requirements*. Geneva: ISO, 2019.

IVANOV, D.; DOLGUI, A. Viability of intertwined supply networks: extending the supply chain resilience angles. *International Journal of Production Research*, vol. 58, n. 10, p. 2904–2915, 2020.

KAPLAN, RS; ANDERSON, SR *Time-Driven Activity-Based Costing: A Simpler and More Powerful Path to Higher Profits*. Boston: Harvard Business School Press, 2007.

NOTTEBOOM, T.; PALLIS, A. Port Economics, Management and Policy: COVID-19 and the impact on ports. Reports/briefs, 2020.

NOTTEBOOM, T.; RODRIGUE, J.-P. Port congestion and the destabilization of supply chains in 2020/2021. *Maritime Economics & Logistics*, 2021.

OECD/ITF – INTERNATIONAL TRANSPORT FORUM. *Policies to Enhance Intermodal Connectivity and Performance*. Paris: OECD Publishing, 2016.

PONOMAROV, SY; HOLCOMB, MC Understanding the concept of supply chain resilience. *The International Journal of Logistics Management*, vol. 20, no. 1, p. 124–143, 2009.

RODRIGUE, J.-P. *The Geography of Transport Systems*. 4th ed. New York: Routledge, 2020.

SEA-INTELLIGENCE MARITIME ANALYSIS. *Global Liner Performance (GLP) Report*. Copenhagen: Sea-Intelligence, 2021.

SHEFFI, Y. *The Power of Resilience: How the Best Companies Manage the Unexpected*. Cambridge, MA: MIT Press, 2015.

SMART FREIGHT CENTER. *Global Logistics Emissions Council (GLEC) Framework*. Amsterdam: SFC, 2019.

UNCTAD – UNITED NATIONS CONFERENCE ON TRADE AND DEVELOPMENT. *Review of Maritime Transport 2020*. Geneva: UNCTAD, 2020.

WORLD BANK; IHS MARKIT. *Container Port Performance Index 2020*. Washington, DC: World Bank, 2020.