Machine Translated by Google
RCMOS - Multidisciplinary Scientific Journal The Knowledge.
ISSN: 2675-9128. São Paulo-SP.

Year VII, v.1 2026 | Submission: 08/02/2026 | Accepted: 11/02/2026 | Publication: 14/02/2026

Numerical simulation and empirical validation in the structural design of critical infrastructures and high-pressure environments.

Numerical simulation and empirical validation in the structural design of critical infrastructures and high-pressure environments

Numerical simulation and empirical validation in the structural design of critical infrastructures and high pressure environments

Lucas Emanuel Soeira holds

a PhD in Science (Mechanical Engineering) from the University of São Paulo (USP); a Master's degree in Mechanical Engineering (USP); and a degree in Mechanical Engineering (UNESP).

SUMMARY

This article discusses the academic foundations that support the indispensable integration between three-dimensional simulation tools (FEA) and destructive laboratory testing protocols. Focused on the design of hulls and pipelines subjected to extreme operating environments, the text analyzes the methodological need to calibrate computational elastic models through rigorous bench data collection. The study delves into the applicability of orthotropic failure criteria and compliance with international standards. The research highlights that computational prediction, when strictly anchored in mechanical instrumentation, enables the safe design of infrastructures subject to continuous fatigue and pressure collapse.

Keywords: Finite Element Analysis; Empirical Validation; Failure Criteria; ASME/DNV Standards; Structural Engineering.

ABSTRACT

This article discusses the academic foundations underpinning the indispensable integration of three-dimensional simulation tools (FEA) with laboratory destructive testing protocols.
Focused on the design of hulls and pipelines subjected to extreme operational environments, the text analyzes the methodological need to calibrate computational elastic models using rigorous bench data. The study examines the applicability of orthotropic failure criteria and their compliance with international standards. The research highlights that computational prediction, when strictly anchored to mechanical instrumentation, enables the safe design of infrastructures subjected to continuous fatigue and pressure collapse.
Keywords: Finite Element Analysis; Empirical Validation; Failure Criteria; ASME/DNV Standards; Structural Engineering.

1. INTRODUCTION

The sizing of projects within the scope of high-tech structural engineering.

Complexity intrinsically deals with variables for which the stochastic margin of failure...

Systemic costs should tend strictly towards zero. The development of strategic infrastructures, which

They range from reinforced polymer submarine pipeline networks to the design of naval hulls.

Subjected to severe hyperbaric conditions, this requires rigorous approval methodologies. These

Mechanical matrices determine the physical viability and environmental safety of ecosystems.

entire operational processes, which compels materials science to continually improve its

This article is published in open access under the Creative Commons Attribution license, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Machine Translated by Google
RCMOS – Multidisciplinary Scientific Journal The Knowledge.
ISSN: 2675-9128. São Paulo-SP.

Year VII, v.1 2026 | Submission: 08/02/2026 | Accepted: 11/02/2026 | Publication: 14/02/2026

ways to predict long-term behavior under harsh conditions.

The widespread consolidation of computational mechanics has driven the progressive abandonment of... rudimentary and conservative analytical equations, based on dimensional simplifications of thin shells, in favor of the extensive use of Finite Element Analysis (FEA). The environment of Virtual modeling has given structural engineers the unprecedented ability to map fronts. stress concentration, transient behaviors and buckling instabilities in complex three-dimensional geometries. These scenarios would be analytically unsolvable if were restricted to the methods of classical strength of materials, developed in the early of the 20th century.

However, the exponential evolution of numerical algorithms for stiffness matrices is not It eliminated the absolute need for empirical validation. On the contrary, the scientific community and regulatory agencies unanimously acknowledge that numerical prediction, operated by In isolation, it lacks legal and structural reliability in non-linear scenarios. material or fluid-structure contact dynamic. Virtual simulation requires feedback. continuous and reliable data, provided by the instrumentation of mechanical testing laboratories.

This article is dedicated to the methodological analysis of this complementary duality that governs design. advanced in engineering. The central objective is to elucidate how the fine correlation between the deformations extracted from physical strain gauges and the color gradients generated in Software processing acts as the main axis for verifying compliance in Approval of heavy equipment. The numerical-experimental correlation is not addressed here. not only as an academic step, but also as a definitive tool for certification of operation.

2. THEORETICAL REVIEW: COMPUTATIONAL FORMULATION AND LIMITS OF THE DIGITAL TWIN

The core of analytical reliability in structures subjected to thermomechanical gradients. The continuous nature of the material resides in the accuracy of the constitutive matrix assigned to the material during the pre-phase. processing in CAE software. Elastic modeling of ductile metal alloys presents an extremely high level of analytical maturity, based on criteria of isotropic flow is widely documented, such as distortion energy theories (von Mises) and maximum shear stress (Tresca). Under these isotropic conditions, the response The elastic curve is governed by reduced variables: Young's modulus and Poisson's ratio.

This article is published in open access under the Creative Commons Attribution license, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Machine Translated by Google
RCMOS – Multidisciplinary Scientific Journal The Knowledge.
ISSN: 2675-9128. São Paulo-SP.

Year VII, v.1 2026 | Submission: 08/02/2026 | Accepted: 11/02/2026 | Publication: 14/02/2026

However, when the scope of the project shifts to the use of composite materials laminates in *offshore* or space defense applications, the complexity of the equations of The contour increases exponentially. Polymers reinforced with continuous fibers have inherently orthotropic characteristics, which implies that their moduli of elasticity... Tensile and compressive stresses, as well as their respective rupture limits, vary depending on the shaft. Loading. The engineer needs to input up to 9 constants into the matrix algorithm. independent elastic curves to correctly define the three-dimensional behavior of a single layer of laminated material

The systemic dependence on such specific input data highlights the critical relevance of this step. of material characterization in a physical laboratory. The modern concept of a "digital twin" *(Digital twin)* assumes that the finite element mesh is not just a rough draft. elegant three-dimensional, but a fully parameterized computational entity for to mirror the actual degradation and flow of the manufactured counterpart. So that this parity If phenomenological events occur, the system must be trained and fed imperatively based on... in reports derived from tensile test coupons and hydrostatic tests.
The iterative calibration process primarily serves to mitigate and reduce uncertainties. inherent to industrial manufacturing methods. Transient defects, such as degrees of cure. incomplete, residual longitudinal stresses induced by cooling processes and Interfacial microcracks cannot be generated in purely ideal formulations. Mathematical. The parallel execution of empirical tests provides the exact numerical basis. which corrects the algorithm's failure asymptotes, allowing the simulated geometry to achieve Highly secure levels of convergence.

3. CORRELATION METHODOLOGY: INSTRUMENTATION IN CRITICAL COMPONENTS

The validation process for industrial piping and encapsulated structures begins, invariably, through the detailed generation of the digital topology and the meticulous discretization of spatial domain in higher-order elements. In the solver environment, the conditions of Restrictions on degrees of freedom and extreme thermal loads are applied to the surfaces. Internal and external simulations are performed to emulate the real operating environment. This step includes the simulation. of the collapsing pressure of the ocean floor confronted simultaneously with the gradients of Expansion caused by the flow of superheated fluids.

This article is published in open access under the Creative Commons Attribution license, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Machine Translated by Google
RCMOS – Multidisciplinary Scientific Journal The Knowledge.
ISSN: 2675-9128. São Paulo-SP.

Year VII, v.1 2026 | Submission: 08/02/2026 | Accepted: 11/02/2026 | Publication: 14/02/2026

The next step involves the physical construction of the apparatus on a real scale, or as...
A scaled-down prototype, which is ostentatiously instrumented using *strain* rosettes.
Gauges (electrical strain gauges), thermocouple sensors, and acoustic emission transducers. The
A pressure vessel or instrumented pipeline is located in hydrostatic test gantries.
governed by servo-controlled hydraulic systems, responsible for applying fatigue cycles
low or high frequency, in strict compliance with defense regulations protocols.
and oil/gas.
The systematic crossing and overlapping of deformation histories read in the modulus of
laboratory data acquisition (DAQ) with the nodal response curve exported by
FEA software reveals the intrinsic correlation ratio of the design. A divergence
perceptible mathematics between the micro-strain (ÿÿ) read by the sensor attached to the part and the
Homologous deformation in the mesh immediately indicates the need to reassess the constraints.
virtual or even recalculate the degree of flexural stiffness of the chosen mathematical formulation.
for the laminate.
The validation of naval hulls and continuous composite piping reaches its climax by
The process involves pushing the structure to its catastrophic limit through the collapse test until rupture *(burst test).*
The laboratory records the exact threshold of overall mechanical stability loss. Reinsertion
This limit on the solver parameters allows for subsequent simulations to be conducted.
focused on the mechanical study of crack propagation *(fracture mechanics),* providing to
engineer's ability to extrapolate the component's lifespan in operation without
costly need to break down samples on a large scale.

4. Fatigue Behavior and Failure Criteria in Materials ORTHOTROPICS

Unlike metals, whose failures generally begin with plastic flow.
macroscopically observable and by the growth of ductile fatigue cracks, the materials
Composites subjected to combined stresses fail through a multiplicity of...
interactive microevents. The collapse of an orthotropic structure is typically preceded by
interlaminar microcracks (matrix cracking), delamination between the fiber and the resin
(debonding), delamination between adjacent layers and, ultimately structurally, the
cataclysmic rupture of tensor fibers. To computationally model this progression of
Damage requires cutting-edge theories.

This article is published in open access under the Creative Commons Attribution license, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Machine Translated by Google
RCMOS - Multidisciplinary Scientific Journal The Knowledge.
ISSN: 2675-9128. São Paulo-SP.

Year VII, v.1 2026 | Submission: 08/02/2026 | Accepted: 11/02/2026 | Publication: 14/02/2026

To mathematically identify in which voltage envelope the first microdefect will occur, FEA programs implement complex interactive formulations, with particular emphasis on Classical Tsai-Wu and Hashin criteria. The Tsai-Wu polynomial criterion, for example, It provides a continuous ellipsoidal failure envelope, indicating whether the part will fail under certain conditions. complex combinations of axial and shear loads. However, this polynomial It depends fundamentally on the precise input of the tensile and compressive strength limits, which They must be raised through prior experimental characterization. (tests on standardized coupons).

Hashin's phenomenological criterion (or Puck's methods) goes beyond simply predicting the moment of collapse and tries to distinguish which of the mechanical modes of ruin is underway (failure). Transverse matrix or primary fiber rupture). The veracity of Hashin's predictions in Three-dimensional nodal meshes are tremendously influenced by mesh sensitivity and...

Considerations for progressive stiffness degradation adopted by the designer. In case these Progressive Damage *Analysis* (PDA) algorithms operate without calibration based on laboratory acoustic emission reports, their forecasts of Survival rates will be fictitious.

The academic and technological challenge in oil pipelines rests heavily on fatigue. oligocyclic pressure induced by internal pump pressure fluctuations or by movements maritime (vortices). The fatigue response in the laminate reduces, day by day, the theoretical margins of the static criterion. It is at this critical point that the merging between the cycle count history of the physical workbench and numerical fatigue routines (based on Miner's cumulative damage rule) It guarantees that the infrastructure system will remain intact for three or four decades. required in ultra-deepwater exploration contracts.

5. INTERNATIONAL STANDARDIZATION AND CERTIFICATION PROTOCOLS (ASME and DNV)

The final link that legitimizes the unrestricted use of numerical simulations associated with testing. Empirical is the overall normative framework imposed by professional authorities and oversight. Internationally, in the industrial pipeline and pressure vessel sector, the *ASME Boiler and Pressure Vessel Code* (notably Section X, focused on *Fiber-Reinforced Plastic Pressure) Vessels* establishes strict rules for the acceptance of components subjected to pressure. The ASME code explicitly requires exhaustive hydrostatic reports to support any

This article is published in open access under the Creative Commons Attribution license, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Machine Translated by Google
RCMOS - Multidisciplinary Scientific Journal The Knowledge.
ISSN: 2675-9128. São Paulo-SP.

Year VII, v.1 2026 | Submission: 08/02/2026 | Accepted: 11/02/2026 | Publication: 14/02/2026

Flexibility in the minimum thicknesses generated in computer-generated reports.
In the context of *offshore* maritime exploration , the independent qualification and
Structural risk management, Det Norske Veritas (DNV), defines the landscape through the
DNV-ST-C501 standard (Composites). This specific standard goes beyond mere design.
prescriptive, underpinning performance *-based design.* It
stipulates partial safety coefficients directly linked to the statistical variance of
data obtained from destructive tests. The greater the reproducibility of the tests of
The better the balance sheet and the better the alignment with the FEA curve, the lower the penalty factors will be.
Due to the uncertainty involved, this allows for significantly lighter projects.
Continuous correlation with these standards prevents interpretive errors in dimensioning.
When the structural engineer develops the numerical model matrix, taking into account the
exact approval limits required by ASCE, API or DNV standards, the report issued
This process transforms into an indisputable legal document of field validation.
Actuarial science protects asset owners against premature losses not covered by insurance.
corporate entities, shielding investor consortia from losses in the billions resulting from
Harmful spill of chemicals into the environment.
In this way, simulation-based compliance, combined with standardized empirical evidence,
It allows for a substantial acceleration of *time-to-market for innovations.* Vases
clad in the latest technologies and lightweight hybrid naval armor receive
The approval of state entities in shorter technical verification cycles. The guarantee of
Integrity is not based on excessive reliance on three-dimensional interfaces.
Aesthetically impeccable, but with scientific traceability demonstrated by the precise matching.
between the world of mathematical data and the irreducible mechanical resistance of the material on the ground.
of tests.

CONCLUSION

The theoretical and practical consolidation of dimensioning in extreme infrastructures reaffirms that
The irreversible advancement of engineering is based on the constant balance between the postulate
Mathematical analysis and empirical refutation. The widespread adoption of finite element analysis.
revealed the intimate and tensional behavior of complex structures, eliminating
definitely the massive dimensioning based on empirical trial and error that prevailed in
macrostructural construction of the last century, replacing it with intelligent allocation and

This article is published in open access under the Creative Commons Attribution license, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Machine Translated by Google

Year VII, v.1 2026 | Submission: 08/02/2026 | Accepted: 11/02/2026 | Publication: 14/02/2026

topological structure of material.

It becomes evident in the literature that the advanced operation of engineering packages aided by Computers require a professional who masters mechanics at the micromolecular level. correct transposition of the resistance of a cylindrical shell of aramid, carbon or naval steel writing lines of numerical code requires a comprehensive mastery of differential equations and of the mechanics of continuous damage. Neglecting this basis implies the risk of obtaining results of graphically flawless tensions in software, but structurally unfounded, artificial and mortals in physical reality.

Testing on an instrumented test bench will undoubtedly remain the definitive validation for Innovations in critical civil, energy, and national defense infrastructure. By demonstrating scientifically, in laboratories with severely controlled atmospheres and loads, that Orthotropic numerical predictions are correct up to the limits of global body collapse.

The evidence suggests that research justifies the decline in the use of heavy metal superalloys in naval shipbuilding. and drives the transition to hydrogen and ultralight compounds.

Future trajectories in this methodological field indicate the increasing incorporation of Machine learning *in* numerical post-processing and evaluation.

Non-destructive. Emerging algorithms will need to absorb thousands of hours of acoustic testing. to autonomously recalibrate the coefficients of the static equations, allowing meshes regenerative technologies that anticipate anomalies based on high-volume predictive statistics.

Revolutionizing the concepts of fatigue monitoring (SHM - *Structural Health) Monitoring).*

In short, an unwavering commitment to the rigor of structural prediction defines reliability. Technology in the ages to come. The constant methodological convergence between exponential power. of the mathematical processing clusters and the precise electrical readings from the load cells This proves that rigorous control of the tensorial integrity of matter will continue to be the cornerstone. inalienable to enable the expansion of large infrastructures with maximum safety. human and environmental.

REFERENCES

KLAUS-JÜRGEN, Bathe. **Finite Element Procedures.** 2nd ed. Watertown: Klaus-Jürgen Bathe, 2014.

TSAI, SW **Composite Materials Design and Testing.** Lausanne: Tech Science Press, 2008.

HASHIN, Z. Failure Criteria for Unidirectional Fiber Composites. **Journal of Applied**

This article is published in open access under the Creative Commons Attribution license, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Machine Translated by Google

Year VII, v.1 2026 | Submission: 08/02/2026 | Accepted: 11/02/2026 | Publication: 14/02/2026

Mechanics, vol. 47, no. 2, p. 329–334, 1980.

ASME BPVC. **Boiler and Pressure Vessel Code, Section X: Fiber-Reinforced Plastic Pressure Vessels.** American Society of Mechanical Engineers, New York, NY, 2023.

DNV-ST-C501. **Composite Components.** Det Norske Veritas - Germanischer Lloyd, Bærum, Norway, 2013.

This article is published in open access under the Creative Commons Attribution license, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.